

POSEIDON
POOL PRODUCTS

IN PARTNERSHIP WITH

Sunline

DECK ROLLER INSTALLATION GUIDE

INSTRUCTIONS

Unpack and place out on a clean suitable area to build your new Deck Roller system. Ensure the area chosen has protection located under lids and rail and other parts. This is to protect from accidental scratching and chips these are not covered under warranty.

The following is required for the building of your system:

- 13mm Socket/ Spanner
- Drill
- Phillips Head Drill Bit
- Rubber Mallet

Your Package includes :


- Lids + Rails Front + Back
- One Side Leg with Gear Box (already located on leg)
- One Side Leg with bearing (already located on leg)
- Strap Kit
- Telescopic Tube
- Self Tapping Screw
- Gearbox Handle

Step 1: Lay Lids and Rails Flat with upside up.

Insert deck support leg into grooves at end of rails, secure with self tapping screws.

Turn upright bolt through decking framework at height required to ensure blanket clearance from ground.





POSEIDON
POOL PRODUCTS

IN PARTNERSHIP WITH

Sunline

Step 2: Place deck leg to each end of bench seat secure into position using rubber mallet secure with screws 2 per end.

Step 3: Connect Telescopic tube assembly together using smaller tube to centre of larger tubes adjust to reach desired length. Place straps for blanket connection using dedicated strap end into the appropriate groove to each end of the telescopic tube as shown.

Step 4: Now secure roller ends into each end under lid correctly located into grooves located on gearbox and bearing adaptor.

Step 5: Now place self-tapping screws on the middle tube where outer tube sits insert screw to intended flat section of tube repeat at each end of tube at the Leg.

Step 6: Adjust straps to level lengths make adjustments to strap as required when connecting solar blanket

Your sunline Deck Roller is complete.

Congratulations now please ensure you register your product warranty with us. Your warranty card details has been provided with product purchased.

